

FAUS AQUA-0

Waterproof surface

Our FAUS AQUA-0 technology with its impermeable surface provides water-resistant laminate flooring for up to 72 hours.

WATER-RESISTANT

Our high-density board is water-repellent treated to ensure that any board expansion is kept minimal and less than <9%.

HERMETIC FIXING

Thanks to our anchored click system, a complete air-tight join is always achieved.

SEALED EDGES

Surfaces are impregnated with paraffin to repel moisture and protect the board.



JOINTGUARD

With its pressed bevelled edging, floor joints are protected by overlay and decorative paper.



Thanks to the protected surface, **FAUS Aqua-0**, our designs that count with the **Jointguard®** technology, guarantee a water resistance period up to **48 hours**.

For the designs counting with the **Interplank®** technology, the water resistance period is of **24 hours**.

If desired, a **24 hours** water resistance period can be added by applying the **Clicseal** joints sealer to the anchoring system (both longitudinally as transversally). Also flexible silicone must be applied to the installation perimeter.*

*This way, the designs with **Jointguard®** will offer a water resistance period up to **72 hours**, as for those with the **Interplank®** technology it will offer a water resistance period up to **48 hours**.

PERFECT FOR

All these technological advances make our FAUS flooring the ideal surface for all types of room and interior-design projects.

